



Straightening and relaxation of HV cables

Together with HV/EHV cable manufacturers Hemi Heating has designed and developed a standard range of heating jackets for straightening and relaxation of High Voltage cables. We offer a complete "Cable straightening set" focusing on safe, exact and steady heating with adjustable temperature up to 100°C. The unique solution with extension pieces gives you the most flexible possibility to cover several different cable dimensions, still with fully homogeneous load density.



Content:

The single sets (CSR 70-115/1 and CSR 40-69/1) consists of three different sizes of heating jackets combinable to heat up different cable dimensions up to Ø115 or 69 mm. Each set also includes a digital temperature control, cables, tool case and RCD.

To reach diameters up to Ø190 mm, add pieces CSR EP25 (see description in page 2).

Each set comes in a large practical bag for easy transportation. As an optional we have an angled Aluminum profile with ratchet straps to make the cable straight.



Technical information:

Operating Voltage:	220-240VAC or 110-120VAC	
Cable range:	Ø70-190 mm or Ø40-69 mm	
Normal heating temperature:	95°C (adjustable setpoint, PID/rampable by time control)	
Built in overtemperature switch:	110°C	
Insulation thickness:	25 mm	
Cables:	5 m power supply, 5 m cable from controller to heating jacket	
RCD:	30mA, Type A	CE
IP rating:	IP44	CC





Straightening and relaxation of HV cables

ticles:		
Item	Cable Ø (mm)	Lenght
CSR 70-115 up to 190		
Single set CSR 70-115/1-1500-230	70-115	1500 mm
Double set CSR 70-115/2-1500-230	70-115	1500 mm
Extension CSR EP25-1500-230		1500 mm
Single set CSR 70-115/1-2000-230	70-115	2000 mm
Double set CSR 70-115/2-2000-230	70-115	2000 mm
Extension CSR EP25-2000-230		2000 mm
Single set CSR 70-115/1-1500-115	70-115	1500 mm
Double set CSR 70-115/2-1500-115	70-115	1500 mm
Extension CSR EP25-1500-115		1500 mm
CSR 40-69		
Single set CSR 40-69/1-2000-230	40-69	2000 mm
Double set CSR 40-69/2-2000-230	40-69	2000 mm
Straightening Aluminum profile		
CSR SP2000		2000 mm

Single set CSR 70-115 covers Ø70-115 mm. To cover larger diameters, use as example below

To cover larger diameters, use as example below:	Other dimensions and
• Up to 140mm: CSR 70-115 + CSR EP25	voltages available on
• Up to 165 mm: CSR 70-115 + CSR EP25 + CSR EP25	request.
• Up to 190 mm: CSR 70-115 + CSR EP25 + CSR EP25 + CSR EP25	

